

STP275 - 20/Wfw Strom-Spannungs- & Leistungs- Spannungskennlinie (285) Mechanische Eigenschaften
Solarzelle Polykristallines Silizium 6 Zoll Anzahl der Zellen 60 (6 x10) Abmessungen 1.650 x 992
x 35 mm (64,96 x 39,1 x 1,4 Zoll) Gewicht 18,3 kg Frontglas 3,2 mm (0,13 Zoll) gehärtetes Glas

Maksymalne zabezpieczenie 20 A Tolerancja mocy 0/+5 W STC: nasłonecznienie 1000W/m², temperatura modulu 25°C AM =1,5; Najlepsze w klasie sprawdzane symulatorem solarnym klasy AAA (IEC 60904-9), dokładność pomiaru od -3/+3% NOCT STP275-20/ Wfw STP270-20/ Wfw STP265-20/ Wfw
Maksymalna moc przy NOCT (Pmax) 200.6 W 198 W 194 W

Wuxi Suntech Power Co., Ltd. Solar Panel Series STP265-275 - 20/Wfw. Detailed profile including pictures, certification details and manufacturer PDF ... STP270-20/ Wfw STP275-20/ Wfw Warranty Product Warranty 12 Years Power Warranty 25 Years of 80.7% Output Power Electrical Data at STC Maximum Power (Pmax) 265 Wp 270 Wp

Painel solar fotovoltaico de 60 células, de excelente qualidade, policristalino, com uma potência de 275 Wp, com 5 busbar, de um dos fabricantes mais reconhecidos mundialmente pela sua qualidade, inovação e fiabilidade. Tolerância positiva. Com estas características, proporciona a melhor relação preço/prestação em instalações de autoconsumo fotovoltaico.

20 A Leistungstoleranz 0/+5 W STC (Standardtestbedingungen): Strahlungsintensität 1,000W/m², Modultemperatur 25 °C, Luftmasse=1,5. Bei Einsatz des führenden AAA-Solarsimulators (IEC60904-9) können Messgenauigkeiten von $\pm 3\%$ erreicht werden. NOCT STP280-20/ Wfw STP275-20/ Wfw STP270-20/ Wfw Maximale Leistung unter NOCT (P_m) 206,3 W ...

NOCT STP275-20/ Wfw STP270-20/ Wfw STP265-20/ Wfw NOCT (Pmax) 200.6 W 198 W 194 W
(V_{mp}) 28.5 V 28.4 V 28.3V (I_{mp}) 7.05 A 6.97 A 6.86 A (Voc) 34.8 V 34.9 V (Isc) 7.5 A 7.42 A 7.32 A

STP 275 - 20 / Wfw Suntech STP 275-20 / Wfw Projektowanie i montaż systemów fotowoltaicznych, dystrybucja komponentów Montaż s.r.o. ... STP275 - 20/Wfw, STP270 - 20/Wfw, STP265 - 20/Wfw. Dane mogą ulec zmianie! Adres siedziby firmy:, U panelarny 10, 772 00 Olomuniec, Republika Czeska

20 A Leistungstoleranz 0/+5 W STC (Standardtestbedingungen): Strahlungsintensität 1,000W/m², Modultemperatur 25 °C, Luftmasse=1,5. Bei Einsatz des führenden AAA-Solarsimulators (IEC60904-9) können Messgenauigkeiten von $\pm 3\%$ erreicht werden. NOCT STP275-20/ Wfw

STP270-20/ Wfw STP265-20/ Wfw Maximale Leistung unter NOCT (?m??) 202,6 W ...

Suntech STP275 - 20/Wfw Home; Suntech STP275 - 20/Wfw 275 Watt POLYCRYSTALLINE SOLAR
MODULE. ?????? ???? : 1 - ???? ????? ??? (????? ??? ???? ?????? ????? Tier 1 ????? ??? ????) ????? ????? ?????
??????? ??? ????? ?? ??? ??? ...

Maximum Series Fuse Rating 20 A Power Tolerance 0/+5 W STC: Irradiance 1000 W/m², module temperature 25 °C, AM=1.5; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% NOCT STP285-20/ Wfw STP280-20/ Wfw STP275-20/ Wfw Maximum Power at NOCT (P_{max}) 210.0 W 206.3 W 200.6 W

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% All technical data at standard test condition

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP280- 20/Wfw STP275 - 20/Wfw STP270 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature (NOCT) 45±2°C Temperature Coefficient of Pmax -0.41 ...

?????????? 20 A ???? 0/+5 W STC:???1000W/m2,???25?,AM=1.5; ??AAA???IEC60904-9
 ??????????????+/- 3% NOCT STP275-20/ Wfw STP270-20/ Wfw STP265-20/ Wfw NOCT???? (Pmax)
 200.6 W 198 W 194 W ?????? (Vmp) 28.5 V 28.4 V 28.3V ???? ...

Current-Voltage & Power-Voltage Curve (275-20) Excellent performance under weak light conditions: at an irradiation intensity of 200 W/m² (AM 1.5, 25 °C), 96.5% or higher of the STC efficiency (1000 W/m²) is achieved Dealer information Mechanical Characteristics Solar Cell Polycrystalline silicon 6 inches No. of Cells 60 (60 ± 10)

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP275- 20/Wfw STP270 - 20/Wfw STP265 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature (NOCT) 45±2°C Temperature Coefficient of Pmax -0.41 %/°C

Web: <https://gennergyps.co.za>