

Wuxi Suntech Power Co., Ltd. Solar Panel Series STP265-275 - 20/Wfw. Detailed profile including pictures, certification details and manufacturer PDF ... STP270-20/ Wfw STP275-20/ Wfw Warranty Product Warranty 12 Years Power ...

STP 275 - 20 / Wfw Suntech STP 275-20 / Wfw Projektowanie i montaz systemów fotowoltaicznych, dystrybucja komponentów Montáze s.r.o. ... STP275 - 20/Wfw, STP270 - 20/Wfw, STP265 - 20/Wfw. Dane moga ulec zmianie! Adres siedziby firmy:, U panelarny 10, 772 00 Olomuniec, Republika Czeska

Suntech STP275-20/Wfw = Suntech STP 275-20 / Wfw The solar panels Suntech STP275-20/Wfw are polycrystalline panels with 275Wp. * New and unused surplus items * Delivery or collection by the customer possible; Please note! The PV modules are remaining stocks. The sale to entrepreneurs takes place under exclusion of any material defect liability.

Maximum Series Fuse Rating 20 A Power Tolerance 0/+5 W STC: Irradiance 1000 W/m², module temperature 25 °C, AM=1.5; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% NOCT STP280-20/ Wfw STP275-20/ Wfw STP270-20/ Wfw Maximum Power at NOCT (Pmax) 206.3 W 200.6 W 198 W

Painel solar fotovoltaico de 60 células, de excelente qualidade, policristalino, com uma potência de 275 Wp, com 5 busbar, de um dos fabricantes mais reconhecidos mundialmente pela sua qualidade, inovação e fiabilidade. Tolerância positiva. Com estas características, proporciona a melhor relação preço/performance em instalações de autoconsumo fotovoltaico.

Wfw STP275-20/ Wfw STP270-20/ Wfw Potenza massima in STC (Pmax) 280 W 275 W 270 W Tensione d'esercizio ottimale (Vmp) 31,3 V 31,2 V 31,1 V Corrente d'esercizio ottimale (Imp) 8,95 A 8,82 A 8,69 A Tensione a circuito aperto (Voc) 38,3 V 38,1 V 37,9 V Corrente di cortocircuito (Isc) 9,41 A 9,27 A 9,15 A

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP275- 20/Wfw STP270 - 20/Wfw STP265 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature (NOCT) 45±2°C Temperature Coefficient of Pmax -0.41 ...

STP275 - 20/Wfk+ STP270 - 20/Wfk+ STP265 - 20/Wfk+. E-mail: sales@suntech-power Temperature Characteristics Nominal Operating Cell Temperature (NOCT) 45±2°C Temperature Coefficient of Pmax -0.41 %/°C Temperature Coefficient of Voc -0.33 %/°C Temperature Coefficient of Isc

0.067 %/°C

20 A Leistungstoleranz 0/+5 W STC (Standardtestbedingungen): Strahlungsintensität 1,000W/m², Modultemperatur 25 °C, Luftmasse=1,5. Bei Einsatz des führenden AAA-Solarsimulators (IEC60904-9) können Messgenauigkeiten von $\pm 3\%$ erreicht werden. NOCT STP275-20/ Wfw STP270-20/ Wfw STP265-20/ Wfw Maximale Leistung unter NOCT (P_{max}) 202,6 W ...

STP280 - 20/Wfw STP275 - 20/Wfw STP270 - 20/Wfw 0/+5W Positive tolerance Positive tolerance of up to 5 W delivers higher output reliability IP68 Rated Junction Box The Suntech IP68 rated junction box ensures an outstanding waterproof level, supports installations in all orientations and reduces stress on the cables. High reliable performance,

STP275 - 20/Wfw 5 PREMIUM Years WARRANTY Weak light Excellent weak light performance More power output in weak light condition, such as haze, cloudy, and morning lower hot spots Reduce the hot spots and minimize panel degradation ** Certifications and standards: IEC 61215, IEC 61730, conformity to CE

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within $\pm 3\%$ STP275- 20/Wfw STP270 - 20/Wfw STP265 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature (NOCT) 45 ± 2 °C Temperature Coefficient of P_{max} -0.41 %/°C

Suntech STP275-20 Wfw poly. Suntech STP275-20 Wfw poly Artikelnummer: 1004. Je bent niet ingelogd . Ben je klant van VDH Solar? Log dan in om een bestelling te kunnen plaatsen. Nog geen klant? Bekijk hier de mogelijkheden ...

Maximum Series Fuse Rating 20 A Power Tolerance 0/+5 W STC: Irradiance 1000 W/m², module temperature 25 °C, AM=1.5; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within $\pm 3\%$ NOCT STP285S-20/ Wfw STP280S-20/ Wfw STP275S-20/ Wfw Maximum Power at NOCT (P_{max}) 210.4 W 206.5 W 202.8 W

Riesige Auswahl Suntech STP275-20/Wfw275Wp - PV-Module jetzt bei Secondsol bestellen. Registrieren. Anmelden. Benutzername. Passwort. 2-Faktor Anmeldung. Nach der Eingabe Ihres Benutzernamens erhalten Sie einen Code per E-Mail! ... STP275-20/Wfw 5.0 (123 Kundenrezensionen) 82,50 ...

Maximum Series Fuse Rating 20 A Power Tolerance 0/+5 W STC: Irradiance 1000 W/m², module temperature 25 °C, AM=1.5; Tolerances of P_{max}, Voc and Isc are all within $\pm 5\%$ NMOT STP285-20/ Wfm STP280-20/ Wfm STP275-20/ Wfm Maximum Power at NMOT (P_{max}) 214.4 W 210.3 W 206.4 W Optimum Operating Voltage (V_{mp}) 29.8 V 29.5 V 29.2 V

Web: <https://gennergyps.co.za>

