

Shoto SDC10-Box5 Model SDC10-Box5 Nominal Capacity 5.12 kWh Usable Capacity 4.1 kWh (Suggest) 5.12 kWh (MAX) Charge Voltage 54.0 - 56.4 V Discharge Voltage 45.0 - 48.0 V Nominal Voltage 51.2 V Charge/Discharge Recommend 50 A(0.5C) Current Max 100 A (1C) Communication Port CAN & RS485

SDC10-Box5 ?????????? ??? 51.2V ??????? ?,????????????????????????????????,???????? ??? 81kWh,????????????? ...

SDC10-Box5 ?????????? ???51.2V????????? ?,????????????????????????????????,????????? ???81kWh,????????????????,?????????????

SDC10-Box 5P SYSTEM FUNCTION /// PRODUCT PARAMETER Model SDC10-Box5(15S) SDC10-Box5(16S) Nominal Capacity (kWh) 4.8 5.12 Depth of Charge Usable Capacity (kWh) 3.84 4.1 Charge Voltage (V) 54.0 56.4 Discharge Voltage (V) 45 48 Nominal Voltage (V) 48 51.2 Max Parallel Quantity (Pcs) Communication Port

SDC10-Box5 series are suitable for 51.2V low voltage ESS. It adopts high safety, high cycle, high reliability and minimalist design. The system can be paralleled, with capacity extended to 81kWh, applied in grid-connected, off-grid, photovoltaic and all kinds of green and low-carbon applications of household ESS. SDC10-Box5 LV Series

SDC10-Box5 ?????????? ??? 51.2V ??????? ?,????????????????????????????????,????????? ??? 81kWh,????????????????,????????????? ?????????????????????????????????

SDC10-Box5 ?????????? ???51.2V????????? ?,????????????????????????????????,????????? ???81kWh,????????????????? ...

Electrical Energy Storage Settings LLC Series GFMJ Series 6-CNF Series GFMHR Series 6-GFMJ Series Smart-Li Series GFM Series 6-GFMHR Series 6-XFMJ Series SDC10-Box5 Battery Storage System 6-SPB Series HP10-Box5 Battery Storage System FTC Series

Web: <https://gennergyps.co.za>